ORIG. STARTED		11-7-41	
DWG. COMPLETED		11-14-41	
ENG. NO.	SUPP.	REVISED	CH.
L-10	505	11-21-41	RC
L-10	534	12-19-41	CL
L-10	605	1-5-42	CL
L-10	634	1-26-42	CL
L-10	858	3-31-42	CL
L-10	1137	6-15-42	CL
L-10	1900	10-21-42	CL
L-10	2178	1-21-43	CL
L-10	2223	2-9-43	CL
L-10	2454	3-25-43	CL
L-10	2826	5-3-43	CL
L-10	3930	11-7-44	CL
L-10	4517	2-21-45	CL
L-10	4588	3-28-45	CL

SPOTWELD SECURELY

GPW16612-HOOD TOP PANEL ASSY

GPW16819-PIN-HOOD HINGE

SECTION A-A
FULL SIZE

GPW16820 HOOD HINGE

℄ OF BODY

VIEW IN DIRECTION OF ARROW-X
FULL SIZE

SPOTWELD SECURELY

SECTION B-B
FULL SIZE

GPW16678-9 REINF-HOOD REAR SIDE

GPW-16676-REINFORCEMENT ASS'Y-HOOD REAR-CENTER

350353-3 CLINCH NUT

GPW-16677 REINF-HOOD REAR-CENTER

SECTION C-C
FULL SIZE

ARC WELD SECURELY

℄ PLAN VIEW

CLEAN & TIN 1"DIA. ON UNDERSIDE OF HOOD-8 PLACES

6

.5

ARC WELD SECURELY

7.5

BEND CORNER OF HOOD TO HOLD HINGE PIN IN PLACE AS SHOWN

30°

FULL SIZE VIEW SHOWING HOOD BENT UP TO RETAIN HINGE PIN

8.

GPN16695 REINF-ALEMITE GUN CATCH ATTACHING HOOD SPOT WELD SECURELY ON LH. SIDE ONLY

340179-SE NUT
SAB302-3-2 WASHER
SB195-SE BOLT
(NOT PART OF THIS ASSY.)

2.65

2.97

X

4.5

.87

17.65

GPN16680-BRACKET ASSY-HOOD ALEMITE GUN ATTACHING

22 DIA. PUNCH 4 HOLES THRU HOOD & REINF LEFT SIDE ONLY

ARC WELD SECURELY

NOTE:
TINNED SPOTS TO BE MASKED DURING PAINTING OPERATIONS

PANEL ASSY- HOOD TOP-WELDING
PAINT-SEE PAINT SPEC.

NOTE:
SAME AS WILLYS OVERLAND PART NO. A-3700

GPW-16610

ALLOWABLE LIMITATIONS ON DIMENSIONS CONTROLLING FINISHED SURFACES ± .015 UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES

DESIGN	SCALE	DRAWN BY	CK.	O.K.		GPW16610
	HALF	WILKIE	EJK	K		